



Determination of the Reduced Costs Carried out in the Process of Operation of Buildings and Constructions

Oleg Korol, Svetlana Bakrunova and Diana Antoniadi

EasyChair preprints are intended for rapid dissemination of research results and are integrated with the rest of EasyChair.

April 8, 2020

Determination of the reduced costs carried out in the process of operation of buildings and constructions

O A Korol^{1,3}, S Y Bakrunova² and D D Antoniadi²

¹Associate Professor, Department of Housing and Communal Services, the National Research Moscow State University of Civil Engineering, Yaroslavskoe shosse 26, Moscow, 129337, Russian Federation

²Student of the National Research Moscow State University of Civil Engineering, Yaroslavskoe shosse 26, Moscow, 129337, Russian Federation

³KorolOA@mgsu.ru

Abstract. In order to reduce operating costs, it is proposed to replace individual elements with modern, more durable and high-tech structures at the stage of repair or overhaul [14]. According to modern requirements of construction, operation and, above all, the modern level of comfort of residents, the parameters of the operational characteristics of housing facilities are evaluated to analyse the total costs. A comparative analysis of operating costs shows the feasibility of innovative transformations in the industry and the need for advanced technologies and materials aimed at ensuring higher social standards of living.

1. Introduction

A building life cycle is the set of processes for developing a business plan, architectural and construction design, construction work, commissioning, followed by cyclical repetitive servicing, maintenance during operation, minor repairs, and it ends with a complete overhaul or demolition. It is considered that the costs that occur during the period from commissioning to waste disposal after demolition exceed the capital construction costs 3-4 times [4].

Long-term operation of the building is carried out based on long-term care plans, functional analysis, diagnostics of energy efficiency, it is also important to carry out building safety diagnostics and compliance check of standards [5]. According to the system of regulatory documents operating in Russia Federation, expenses of ongoing activities for the operation of buildings and structures as estimated by real estate experts, in relation to initial cost of an object can be:

- providing buildings with utility services - 3-5%;
- maintenance and repair of construction structures and building engineering systems - 1-3%;
- sanitary maintenance - 0,4-0,6%;

Generally, the cost of operated buildings and structures for the year can be up to 10% of the cost of their construction [11-16].

In order to prevent depreciation of the building, increase its consumer values and lifespan, maintenance works are periodically carried out. During long-term operation, modernisation and major repairs may be required, for example, due to the deterioration of the buildings or changes in the requirements for it [6-8].

Overhaul is a replacement or restoration of physically worn-out building structures and elements in order to improve the condition of the building in general. Also produced technical service and maintenance performed by the management organization to ensure the long-term and strength properties of structural elements (for example, checking the suitability of hoods for sewage systems, the presence of working traction in smoke ducts, lubricating metal roof elements, etc.) [1-4].

The composition and scope of repair and construction work is determined on the basis of data from field surveys of buildings with the subsequent release of a technical report by a specialised organisation, and the cost of repairs - at the current estimated standards and prices.

The obligatory general list of overhaul measures includes: roof repair, facade repair, repair of house engineering systems (electricity, gas, water, heat, drainage), repair or replacement of elevator equipment, repair of elevator shafts, repair of basements, foundation repair. For their implementation, both traditional and innovative technologies can be used [3].

Maintenance work is a repair, which is carried out annually to eliminate premature wear to exclude minor damage and defects, i.e. has a preventive nature.

The scope of work on current repairs according to the guidelines for the maintenance and repair of the housing stock includes: updating the architectural elements of the building, sealing individual sections of joints; local painting of the facade, walls and ceiling indoors; pipe painting; minor repairs of railings; replacement of lighting; garbage chute repair, etc., i.e. repairs are made locally [7].

In order to minimize the costs of these processes, appropriate measures to improve the technical performance properties of structural elements. Through the introduction of a more wear-resistant designs and materials, their service life increases and thereby reduces the number of repairs for a certain period of time of operation of buildings and structure. For example, the use of more durable clay bricks of grade 100 instead of grade 50 increases the cost of 1 m³ of masonry by 2.4 rubles. Parquet floors, exterior walls covering of buildings with ceramic tiles are also more expensive than less durable plank floors and plastering the exterior walls, but annual repair and maintenance costs are reduced [10-11]. The less often structural elements are repaired and the cost of these repairs is minimal, the greater is the optimal service life of the elements and the building as a whole.

2. Materials and methods

Expenses on the stage of operation of buildings and structures when considering the structural elements, the length of service is equal to the life of the building as a whole, are completely determined for the entire period of time of operation and are calculated as follows:

$$Z_3 = \frac{K_3}{\alpha_t} + \sum_1^{\gamma_{kp}-1} \frac{C_{kp}}{\alpha_t} + \sum_1^{T_c} \frac{C_{tp}}{\alpha_t} + \sum_1^{\gamma_{3k}-1} \frac{C_{3k}}{\alpha_t} \quad (1)$$

where K_3 - the specific capital investment in the repair base or the rate of the main measures taken, applied in the implementation of repair and construction works;

C_{kp} - cost of one overhaul of building structures;

C_{tp} - the cost of one ongoing repair of structural elements;

C_{3k} - expenses necessary to maintain the durability of structures, as well as expenses for the technical maintenance of buildings or structures;

t - the period of the overhaul, as well as the cost of restoration and maintenance of structural elements.

$\gamma_{kp} - 1$ - the total number of overhauls for the period of operation of buildings and structures is calculated by the formula:

$$\gamma_{kp} - 1 = \frac{T_c}{T_{kp}} - 1 \quad (2)$$

where T_{kp} - cyclicity overhauls compared structures.

γ_{3k-1} - the number of repairs, to restore and maintain the quality and durability of structures, calculated as follows:

$$\gamma_{3k-1} = \frac{T_c}{T_{3k}} - 1 \quad (3)$$

where T_{3k} - the cyclicity of cost execution of restoring and maintaining the quality of structural elements.

The elements of the cost components in the formula (1) carried out at the stage of operation of buildings and structures lead to the period of the beginning of operation when divided by the reduction coefficient α_t .

3. Results

The values of the coefficient $\frac{1}{\alpha_t}$ for different periods of implementation of costs and the standard of reduction $E = 0.1$ are shown in table 1, where t is the period in years between expenditures at the time of development and production of the object and the beginning of operation of the building.

Table 1. Coefficient value $\frac{1}{\alpha_t} = \frac{1}{(1+E)^t}$ (when $E=0,1$).

Years	Decades						
	0	1	2	3	4	5	6
0	1	0,385	0,149	0,057	0,022	0,008	0,003
1	0,909	0,35	0,135	0,052	0,02	0,007	0,002
2	0,826	0,318	0,123	0,047	0,018	0,007	0,002
3	0,751	0,29	0,111	0,043	0,016	0,006	0,002
4	0,683	0,263	0,101	0,039	0,015	0,005	0,002
5	0,621	0,239	0,092	0,035	0,013	0,005	0,002
6	0,564	0,217	0,084	0,032	0,012	0,004	0,002
7	0,513	0,198	0,076	0,029	0,011	0,004	0,002
8	0,466	0,18	0,069	0,026	0,01	0,003	0,002
9	0,424	0,163	0,063	0,024	0,009	0,003	0,001

The presented dependence of the coefficient $\frac{1}{\alpha_t}$ for various periods of operation is illustrated on the graph (figure1).




Figure 1. Dependence of the coefficient for various periods of operation.

For example, at $t = 7$ years $\frac{1}{\alpha_t} = 0,51$, $t = 35$ years $\frac{1}{\alpha_t} = 0,035$, $t = 60$ years $\frac{1}{\alpha_t} = 0,003$.

The beginning of first year of operation $t = 0$ $\frac{1}{\alpha_t} = 1$, and at $t = 70$ years and more $\frac{1}{\alpha_t} = 0,001$.

With absence of direct or calculated data on the expenses of current repairs, the cost of annual current repairs can be determined by the formula:

$$C_{\text{ТР}} = q \frac{(C_{\text{Д}} - C_{\text{ЗК}})}{T_{\text{КР}}} \quad (4)$$

where q is a coefficient depending on the surface modulus of the structures M_n , which is equal to the ratio of the external surface area of the structures (m^2) to its volume (m^3).

For powerful large-sized structures (bridge supports, building foundations), the surface modulus $M_n \leq 5$, and the coefficient $q = 0.04$.

For metal non-massive structures: at $M_n > 5$, the coefficient $q = 0.35$.

The costs shown in formula (1) appear several times during the lifetime of the building, therefore, it is recommended to apply for each type of expenditure produced a total coefficient of reduction of one-time costs for ease of calculation, which is calculated as follows:

$$\mu = \sum_{t_{\text{н.э}}}^{T_{\text{с}} - t_{\text{н.э}}} \frac{1}{\alpha_t} \quad (5)$$

where $t_{\text{н.э}}$ - he frequency of production of costs presented in formula (1) at the stage of operation of buildings or structures, in years;

t - years of spending.

When using the total reduction coefficient, the total costs incurred during operation are calculated by the formula:

$$Z_3 = K_3 + C_{\text{кр}}\mu_{\text{кр}} + C_{\text{тр}}\mu_{\text{тр}} + C_{\text{зк}}\mu_{\text{зк}} + C_{\text{п}}\mu_{\text{п}} \quad (6)$$

The planned nature of the maintenance and repair of the building allows to slightly reduce these costs and at the same time increase the life of the unit.

4. Conclusion

In order to increase energy efficiency it is necessary to consider the building comprehensively - throughout the entire period from its construction to demolition, i.e. as an object not only of construction but also of operation. Also, starting from the stage of developing a business plan, it is important to consider strategic issues related to the functioning of the building, as well as the fluctuating needs of the company located in it when planning repairs and upgrades, since all this affects the cost recovery [13-14].

References

1. Korol O.A. The conceptual basis for the formation of the regulatory framework for the overhaul of the common property of multi-apartment residential buildings // BST: Bulletin of construction equipment. 2018, no 11 (1011), pp. 20-21. (In Russian)
2. Korol O.A. Kuznetsov G.S., Multicriteria analysis of measures during the overhaul of apartment buildings //Real estate: economics, management. 2017, no 1, pp. 57-61. (In Russian)
3. Schreiber K.A., Korol O.A. Evaluation of the durability indicators of structural elements and systems when planning the overhaul of the common property of apartment buildings. In the collection: System engineering of construction. Cyberphysical Building Systems - 2019 Collection of Materials of the All-Russian Scientific and Practical Conference. 2019.S. 574-577.
4. Grabovoi P.G., Korol E.A., Grabovoi K.P., Semenov V.N., Kagan P.B., Pugach E.M. Innovative technologies for developing a program-targeted energy-saving management system in construction. Moscow, 2014.
5. Korol E.A., Kagan P.B., Khorkina J.A. Ways to increase the effectiveness of ongoing housing investment programs. Building materials, equipment, technologies of the 21st century. 2011. No. 8 (151). S. 16-17
6. Korol E.A., Rubtsov I.V., Kukhta A.V., Chetverik N.P. The principles of building monitoring systems for high-rise buildings and structures. High-rise buildings: a magazine of high-rise technologies. 2008. No. 5. P. 123-125.
7. Telichenko V.I., Korol E.A., Kagan B.P., Komissarov S.V. Modern management methods for regional and city housing construction and reconstruction programs. In the collection: Proceedings of the General Meeting of the Russian Academy of Architecture and Building Sciences 2007. P. 444-448.
8. Telichenko V.I., Korol E.A., Kagan P.B., Komissarov S.V., Pavlov A.S., Shirshikov B.F., Yarovenko S.M., Bachurina S.S. Solving the problems of network planning and management of urban construction programs. Building materials, equipment, technologies of the 21st century. 2005. No. 3 (74). S. 12-14.
9. Perfilova E.A., Korol E.A., Ostyakova A.V. Analysis of the operational characteristics of the updated housing stock as a result of renovation. In the collection: Construction - Formation of the Living Environment XXI International Scientific Conference: a collection of materials from the seminar "Youth Innovations". 2018.P. 357-359.
10. Korol E.A., Zhuravleva A.A. Algorithm for the selection of rational organizational and technological solutions in the construction of low-rise residential buildings. BST: Bulletin of construction equipment. 2018.No 7 (1007). S. 51-53.

11. Dudina A.G., Korol E.A. Energy-efficient aspects of the renovation of the housing stock of Moscow. In the collection: Construction - Formation of the Living Environment XXI International Scientific Conference: a collection of materials from the seminar "Youth Innovations". 2018.S. 324-326.
12. Korol, E., Shushunova, N. Multi-Criteria Evaluation of the Organizational and Technological Options for Green Roof Systems Installation. IOP Conference Series Materials Science and Engineering 471:08201, February 2019 DOI: 10.1088/1757-899X/471/8/082011
13. Korol O.A. The impact of energy-corrective measures at the design stage of construction projects. MATEC Web of Conferences. 2018
14. Korol, O., Dudina, A. Features of Calculation of Consumption of Fuel and Energy Resources for Heating of Temporary Buildings and Structures on Construction Area. IOP Conference Series: Materials Science and Engineering. 2019
15. Korol, O., Dudina, A. Engineering and Technical Support of Territories for Implementation of Renovation Projects of the Housing Stock. E3S Web of Conferences. 2019
16. Korol, O., Kustikova, Y. Principles and methods for ensuring safe operation of high-rise buildings. E3S Web of Conferences. 2018
17. Mailyan L.R. Calculation of shallow polymer shell taking the creep into account. Matec web of conferences, 106, 04010 (2017) SPBWOSCE-2016. DOI:10.1051/ma-tecconf/201710604010
18. Mailyan L.R. Calculation of the rotation shells on axisymmetric load taking creep into account. Matec web of conferences, 106, 04011 (2017) SPBWOSCE-2016. DOI:10.1051/ma-tecconf/201710604011
19. Lyapunsova, E., Belozerova, I., Drozdova, I., Korol, O. Safety in construction in the field of investment in urban infrastructure. E3S Web of Conferences.
20. Evseev V.O., Borkovskaya V.G., Barkhi R. Modelling the reliability of the implementation of the schedule building work. IOP Conf. Series: Journal of Physics: Conf. Series 1425 (2020) 012175. doi:10.1088/1742-6596/1425/1/012175